

Universal Loud Sounding Alarm



This versatile unit, in the same-sized case as our K3507 tone ringer, replaces the Type-C Alarm. There is provision for two exchange lines via separate RJ11 sockets. Four different selectable alarm-tones are provided for each exchange line. All other connections to and from the unit are via screw terminals. Requires K3505 horn speaker. Other peripheral devices such as strobe lights, PIR sensors, doorbells, reed-relays, PA amplifier inputs etc can be connected. Supplied with a 12V DC power supply which is also used to provide 12V power for strobe-light operation. The maximum volume of the Universal Loud Sounding Alarm in conjunction with our K3505 Horn Speaker is 110dB. The unit has a REN of 0.1. Dimensions 115(W) x 155(H) x 35(D)mm.

CAT #	ITEM
K3509	Universal Alarm
K3504BLU	Strobe Light
K3505	Horn Speaker

Horn Speaker



15 watt horn speaker suitable for connection to the K3507 Tone Ringer or to the K3509 Universal Loud Sounding Alarm. The 350mm figure-8 cable has tinned ends for easy connection. IP4, splash-proof. Color is white.

CAT #
K3505

Strobe Light



This 12 volt, 3 watt strobe light is suitable for connection to our Universal Loud Sounding Alarm or for use with alarm systems, indicator-boards etc. Three lugs allow mounting to any surface. Two 550mm conductors exit from the centre rear of the unit and have tinned ends for easy termination.

CAT #	LENS COLOR
K3504BLU	Blue

Tone Ringer



Robust extension tone ringer with volume and pitch controls and an on/off switch. Connection to the exchange line is via either screw terminals or modular socket. Unit has a built-in speaker. An optional 15 watt horn speaker (connected via screw terminals) is available for more directional signalling of incoming calls. Maximum volume 98dB. This unit has a REN of 1.9. Dimensions 115(W) x 155(H) x 35(D)mm.

CAT #	ITEM
K3507	Tone Ringer
K3505	Horn Speaker

Extra Loud Bell



Extra loud extension bell with volume control, ideal for use in noisy environments or large sites. Modular sockets are fitted to allow in-line connection. Modular line cord and mounting bracket are included. REN 2.8.

CAT #
K3501

Extension Bell



605 plug connects directly into telephone line socket and mechanical bell rings loudly when incoming calls are received. Supplied with a 10 metre cord which connects to bell using a modular socket. On/off switch allows bell to be disabled. REN 1.0.

CAT #
K3500

Nursecall Pendant



Nursecall button with soft PVC pendant for hospital and aged care services. Plug type and wiring can be custom made to suit host equipment. Standard color is white cable with green button.

CAT #	PLUG	LENGTH
K3811	6.3mm Stereo Phono	3 Metre
K3811-005	6.3mm Stereo Phono	5 Metre
K3811-008	6.3mm Stereo Phono	8 Metre
K3832	RCA	2 Metre
K3804GRN	Spare Green Button	

Nursecall Pressure Pad



Nursecall pressure pad for hospital and aged care services. Plug type and wiring can be custom made to suit host equipment. Standard color is white.

CAT #	PLUG	LENGTH
K3820	6.3mm Stereo Phono	2 Metre

Check our website for installation manuals & brochures
www.accesscomms.com.au