

TELEMASTER[®]

LINESMAN'S TEST TELEPHONE

Cat # T0113

Features :

Speakerphone
High Impedance Coupling
Mute Switch
LED Line Polarity Monitoring
LED Line Voltage Monitoring
Tone/Pulse Dialing
PABX Pause Button
Volume Control
Last Number Redial
13 Memory Stores
Battery Saving Operation
Belt Clip



Package includes:

Test Telephone
Test Clips / Modular Plug
Modular Coupler
IDC Test Cord
Battery

Specifications

Loop Limit	2K Ω max at 48V DC (nominal 20mA minimum loop current)
DC Resistance	300 Ω typical (Talk mode)
Monitor Impedance	39K Ω nominal at 1KHz
Rotary Dial Output	10pps \pm 0.8pps
	Pulse Rate
	Percent Break
	Interdigital Pause
	Leakage During Break
	Tone Frequency Error
	Tone level
	High/Low Tone Difference
DTMF Output	\pm 1.2% maximum
	+8 \pm 2dBm combined (typical)
	4dB maximum
Memory Dialling	13 memories (including M1) plus LNR
	16 digits per memory
	4 seconds
Monitor Amplifier	Transistor
Power Source	9V battery provides 25 hours continuous use (typical)
Speaker levels	Electronically adjustable
Auto Power Shut-off	After 5 minutes of no audio signal
Dimensions	Length
	Width
	Height
Weight	635g (typical)
Environmental	Temperature Range
	Altitude
	Relative Humidity

Distributed By:

ACCESS
COMMUNICATIONS PTY LTD
www.accesscomms.com.au

Sydney

Tel: (02) 9414 8888
Fax: (02) 9414 8800

Melbourne

Tel: (03) 9330 8333
Fax: (03) 9330 8330

Brisbane

Tel: (07) 3308 5555
Fax: (07) 3308 5500